

Industrial Single Board Computer

3.5 Inch Mini board

LE-37A

Intel® Sandy Bridge Processor 807UE/827E/847E with DDRIII
SO-DIMM, CRT, DVI, LVDS, Gigabit LAN, USB2.0, HD Audio,
Serial ATAIII, PCIE mini card, LPC, mSATA



Form Factor	3.5 Inches Embedded Mini board
CPU	Intel® Celeron® Processor 807UE 1.0GHz (LE-37ANB) Intel® Celeron® Processor 827E 1.4GHz (LE-37AC6) Intel® Celeron® Processor 847E 1.1GHz (LE-37ABU) Package type : FCBGA1023
Memory	1 x DDRIII SO-DIMM 1066/1333 MHz up to 4GB (LE-37ANB) 1 x DDRIII SO-DIMM 1066/1333 MHz up to 8GB (LE-37AC6 / LE-37ABU) Support Non-ECC, unbuffered memory only
Chipset	Intel® HM65
Real Time Clock	Chipset integrated RTC with onboard lithium battery
Watchdog Timer	Generates a system reset with internal timer for 1min/s ~ 255min/s
Power Management	Supports ACPI 3.0 compliant
Serial ATA Interface	2 x serial ATAIII interface with 600MB/s transfer rate
Integrated Graphics	Intel® integrated extreme HD graphics Technology
VGA Interface	Onboard DSUB15 connector for VGA interface
LVDS Interface	Onboard 24-bit Dual channel LVDS connector with +3.3V/+5V/+12V supply
DVI interface	Onboard DVI with 20-pin connector
Audio Interface	REALTEK ALC888 HD Audio
LAN Interface	1 x Intel® 82579LM Gigabit Ethernet controller
GPIO Interface	Onboard programmable 8-bit Digital I/O interface
Extended Interface	2 x PCIE mini card(Optional support mSATA(SATAII) for Mini_Card2)
Internal I/O Port	1 x RS232/485/422, 1 x SMBUS, 1 x GPIO, 4 x USB2.0, 1 x IrDA, 2 x Serial ATAIII, x 1x LPC, 1 x HD Audio, 1 x DVI , 1 x LVDS, 1 x CN_INV
External I/O Port	1 x PS/2, 1 x RJ45, 1 x VGA, 2 x USB2.0, 1 x RS232
Power Requirement	Full ranged 9V~24V(±5%) DC Input
Dimension	146mm x 101mm
Temperature	Operating within 0~60 centigrade Storage within -20~85 centigrade

Taiwan Commate Computer Inc.

19F, NO. 94, Sec. 1, Shin Tai Wu Rd., Hsi Chih, Taipei Shien, Taiwan.

TEL: +886-2-26963909

Website:www.commell.com.tw

FAX: +886-2-26963911

E-mail:info@commell.com.tw

 **COMMELL**

Stage For Your Success

Ordering Code

LE-37ANB	Intel® Celeron® Processor 807UE with Onboard VGA, LVDS, DVI, Giga LAN, USB2.0, HD Audio, SATAIII, SMBUS, LPC, GPIO, PCIE mini card
LE-37ANBS	Intel® Celeron® Processor 807UE with Onboard VGA, LVDS, DVI, Giga LAN, USB2.0, HD Audio, SATAIII, SMBUS, LPC, GPIO, PCIE mini card, mSATA
LE-37AC6	Intel® Celeron® Processor 827E with Onboard VGA, LVDS, DVI, Giga LAN, USB2.0, HD Audio, SATAIII, SMBUS, LPC, GPIO, PCIE mini card
LE-37AC6S	Intel® Celeron® Processor 827E with Onboard VGA, LVDS, DVI, Giga LAN, USB2.0, HD Audio, SATAIII, SMBUS, LPC, GPIO, PCIE mini card, mSATA
LE-37ABU	Intel® Celeron® Processor 847E with Onboard VGA, LVDS, DVI, Giga LAN, USB2.0, HD Audio, SATAIII, SMBUS, LPC, GPIO, PCIE mini card
LE-37ABUS	Intel® Celeron® Processor 847E with Onboard VGA, LVDS, DVI, Giga LAN, USB2.0, HD Audio, SATAIII, SMBUS, LPC, GPIO, PCIE mini card, mSATA

Taiwan Commate Computer Inc.

19F, NO. 94, Sec. 1, Shin Tai Wu Rd., Hsi Chih, Taipei Shien, Taiwan.

TEL: +886-2-26963909

Website: www.commell.com.tw

FAX: +886-2-26963911

E-mail: info@commell.com.tw



Stage For Your Success