

Product Test Report



Product Name	MPX-6864
Product Version	A
Issued Date	2011.08.12
Report Edition	1.0
Testing Engineer	RICK

1. Support to board list

Chipset	Board	Result	Remark
Intel(R) Atom(TM) N270 Intel(R) 945GSE Express ICH7M	LV-67D	PASS	
	LV-67DD	PASS	
	LV-67DX	PASS	
	FE-97GTXG	PASS	
	FE-97GTXG2	PASS	
	FE-97GTXDG	PASS	
	FE-97GTXDG2	PASS	
Intel(R) Atom(TM) D510/N450/D410 ICH8M	LP-170 A/G/H	PASS	
	LV-67E A/G/H	PASS	
	LE-376 A/G/H	PASS	
	HE-772 A/G/H	PASS	
Intel(R)Atom(TM) Z510P/PT/Z520PT SCH US 15WP/WPT	LP-171 D/T	PASS	
	LE-375 D/T/X	PASS	
Intel(R) GM45 Express ICH9M	LS-373	PASS	
	LS-573TX	PASS	
	LS-573TXD	PASS	DVI disable
	LV-67B	PASS	
	HS-771	PASS	
	HS-873PXDG	PASS	DVI disable
	HS-873PXDG2	PASS	DVI disable
	HS-873PXG	PASS	
	HS-873PXG2	PASS	
	FS-97EXG	PASS	
	FS-97EXG2	PASS	
	FS-97EXDG	PASS	
	FS-97EXDG2	PASS	
Intel(R) Q57 Express	LV-67C	PASS	
	MS-C72	PASS	
Intel(R) QM67 Express	LV-67H	PASS	

2. Software

Software	OS	Result
TW68XX SDK	Window XP SP2	PASS

3. Test equipments

Play equipment	Result
LG DV276 DVD player	PASS
Camera	PASS

4. Cable:



1 x 10-pin DF14 to D-sub 9 Cable
(OALDB9-BR4)



1 x 4-ch BNC Video input &
4-ch RCA Audio input Cable
(OALDB9-BR4)

5. Operating temperature: 0°C~60°C